

Insulation shell for EPIV / Belimo Energy Valve™

- only for non-condensing applications
- easy mounting thanks to velcro strip
- can also be mounted/dismounted subsequently



Type Overview

Type	DN	Suitable for	Weight
EXT-OC-ZEP15	15	EP015.. / EV015..	0.04 kg
EXT-OC-ZEP20	20	EP020.. / EV020..	0.05 kg
EXT-OC-ZEP25	25	EP025.. / EV025..	0.06 kg
EXT-OC-ZEP32	32	EP032.. / EV032..	0.07 kg
EXT-OC-ZEP40	40	EP040.. / EV040..	0.08 kg
EXT-OC-ZEP50	50	EP050.. / EV050..	0.11 kg

Technical data

Functional data	Thermal conductivity	0.035 W/mK
Materials	Used Materials	Polyethylen foam (PE-3015 acc. EN 12667:2001 / EN 12664:2001)

Safety notes



- This accessory has been designed for use in stationary heating, ventilation and air-conditioning systems and must not be used outside the specified field of application, especially in aircraft or in any other airborne means of transport.
- Only authorised specialists may carry out installation. All applicable legal or institutional installation regulations must be complied during installation.
- The accessory may not be disposed of as household refuse. All locally valid regulations and requirements must be observed.